

S-840



We Are Passionate About Your Success!

Faster.

- Increase daily volume without increasing man-hours.
- Design allows for unlimited pull back distance.
- Screeds up to 5,000 square feet per hour.

Flatter.

- Patented soft-landing feature makes perfect landings.
- Automatic column-block protection.
- Superior Floor Levelness (FL) performance.

Fewer.®

- Automated screed process means fewer man-hours per project.
- Screed at a lower cost per square foot vs. other methods.
- Low operating and maintenance costs.

Leading Edge Laser Control System

Leading Edge OASIS Laser Control System provides faster elevation and self level response.

- Customized for the S-840, the new control system allows faster elevation & SLS response.
- Proportional valves for fast, accurate elevation control.
- Live calibration for consistent unsurpassed performance.



S-840 Laser Screed® Concrete Leveling Head

- Choose between a 6' (1.8m) or 8' (2.4m) head option to increase productivity.
- New auger offset also increases productivity.
- Performs well with slump as low as 3.5" (8.9cm)

S-840 Raking Head

- Available in a 6' (1.8m) or 8' (2.4m) head option to increase productivity.

- Rake more concrete in less time with a single operator

S-840 Sub-grade Head

- Used for fine grading sub-base. Improves concrete yields turning previously wasted concrete cost into profit.
- 3-D Profiler System® compatibility
- Increase Laser Screed® utilization.

**For more information:
Call Inside Sales at +1-239-210-6519.**

S-840



We Are Passionate About Your Success!

Equipment Specifications

Length	9'7" (2.92m)
Width	43 1/4" (1.1m)
Height	55" (1.4m)
Ground Clearance	11.5" (.3m)
Head Clearance	13.75" (.35m)
Engine	Robin 20.5 hp EH65
Start	Electric start
Propel	4 wheel drive with hydraulic motors
Propel Control	Proportional joystick and valve driving hydraulic motors
Elevation Control	Dual Hydraulic Cylinders
Steering Control	Proportional joystick and valve driving a hydraulic cylinder
Laser Controls	Trimble SSR2 Laser Receivers
Machine Weight	1,548 lbs (702 kg) w/Laser Screed Head attached
Note:	These specs are based on 8' (2.4m) Screed Head. 6' (1.8m) versions are also available contact your Somero sales rep for more details.
Standard Tire Ground Pressure	38 psi (262 kpa)
ATV Tire Ground Pressure	9.8 psi (67.6 kpa)

Corporate Offices: 16831 Link Court, Fort Myers, FL 33912 - **Phone: +1.239.210.6500 Fax: +1.239.210.6600**

Operation Office: 46980 Highway M26 Houghton, MI 49931 - **Phone: +1.906.482.7252**

Chesterfield England: Broombank Road, Chesterfield Trading Estates, Derbyshire, UK S41 9QJ - **Phone: +44.1246.454455**

Shanghai China: No. 2399, Zhaochong Highway, Qingpu District, Shanghai. 201706, China - **Phone: +86-21-60259766**

India Office: 573, 3rd Floor, Main Road Chirag Delhi, New Delhi - 110017, India

SOMERO ENTERPRISES INC. WWW.SOMERO.COM

Copyright 2015 Somero Enterprises, INC. © All rights reserved